

100% oil-free compressed air in its purest form

## SCROLLline Compressors 7,5–30,0 kW




Made in  
Germany

# Nº1

The first of its  
performance class!



**oil-free**  
Made in Germany 



**100% oil-free compressed air in its purest form**

# SCROLLline Compressors 7,5–30,0 kW



Made in  
Germany

We are happy to introduce to you the latest innovation at RENNER. The SCROLL range has been expanded by a new performance class. As the first company, RENNER now offers SCROLL compressors from 1.5 to 30 kW!

## The new SCROLL model at a glance:

- ✓ **Powerful**
- ✓ **Compact**
- ✓ **Maintenance friendly**
- ✓ **Versatile use**
- ✓ **Different controls for individual applications**
- ✓ **Efficient, sturdy motors**

Any questions? Do not hesitate to contact us!

| Overview of the new SCROLL Industry models |                            |     |             |      |                               |                                    |                       |                        |              |
|--------------------------------------------|----------------------------|-----|-------------|------|-------------------------------|------------------------------------|-----------------------|------------------------|--------------|
| Model                                      | Free air delivery<br>8 bar |     | Motor power |      | Dimensions<br>L x W x H<br>mm | Compressed<br>air outlet<br>inches | Noise level<br>dB(A)* | Air receiver<br>litres | Weight<br>kg |
|                                            | l/min                      | cfm | kW          | HP   |                               |                                    |                       |                        |              |
| SL-I 7,5                                   | 890                        | 31  | 7.5         | 10.0 | 760 x 550 x 920               | 3/4"                               | 69                    | –                      | 140          |
| SLD-I 7,5                                  | 890                        | 31  | 7.5         | 10.0 | 1410 x 570 x 1550             | 3/4"                               | 69                    | 250                    | 225          |
| SLK-I 7,5                                  | 890                        | 31  | 7.5         | 10.0 | 1015 x 550 x 920              | 3/4"                               | 69                    | –                      | 170          |
| SLDK-I 7,5                                 | 890                        | 31  | 7.5         | 10.0 | 1410 x 570 x 1550             | 3/4"                               | 69                    | 250                    | 250          |

| Overview of the new SuperSilent models |                            |     |             |      |                               |                                    |                       |                        |              |
|----------------------------------------|----------------------------|-----|-------------|------|-------------------------------|------------------------------------|-----------------------|------------------------|--------------|
| Model                                  | Free air delivery<br>8 bar |     | Motor power |      | Dimensions<br>L x W x H<br>mm | Compressed<br>air outlet<br>inches | Noise level<br>dB(A)* | Air receiver<br>litres | Weight<br>kg |
|                                        | l/min                      | cfm | kW          | HP   |                               |                                    |                       |                        |              |
| SL-S 7,5                               | 890                        | 31  | 7.5         | 10.0 | 910 x 550 x 920               | 3/4"                               | 63                    | –                      | 160          |
| SLD-S 7,5                              | 890                        | 31  | 7.5         | 10.0 | 1410 x 570 x 1550             | 3/4"                               | 63                    | 250                    | 245          |
| SLK-S 7,5                              | 890                        | 31  | 7.5         | 10.0 | 1165 x 550 x 920              | 3/4"                               | 63                    | –                      | 190          |
| SLDK-S 7,5                             | 890                        | 31  | 7.5         | 10.0 | 1410 x 570 x 1550             | 3/4"                               | 63                    | 250                    | 270          |
| SLM-S 15                               | 1780                       | 63  | 15.0        | 20.0 | 1400 x 920 x 1020             | 1"                                 | 65                    | –                      | 485          |
| SLM-S 22,5                             | 2670                       | 74  | 22.5        | 30.0 | 1400 x 920 x 1890             | 1"                                 | 68                    | –                      | 840          |
| SLM-S 30                               | 3560                       | 126 | 30.0        | 40.0 | 1400 x 920 x 1890             | 1"                                 | 71                    | –                      | 975          |
| SLDM-S 15                              | 1780                       | 63  | 15.0        | 15.0 | 1970 x 920 x 1767             | 1"                                 | 65                    | 500                    | 695          |

\* as per DIN EN ISO 2151:2009

